








### Gummi-Räder

Rad: Radkörper aus Stahlblech, glanzverzinkt.  
 Ausgerüstet mit Gummibereifung.






### Rubber wheels

Wheel: Wheel centre out of steel, glossy zink-plated. With rubber tyre.



Räder Wheels Code:						
	mm	mm	mm	mm	Kg	
W8/1/80	80	30	15	39	50	
W8/2/80	80	30	12	40	50	
W8/3/80	80	30	8	38	50	
W8/1/100	100	30	15	39	70	
W8/2/100	100	30	12	40	70	
W8/3/100	100	30	8	37	70	
W8/1/125	125	37	15	49	100	
W8/2/125	125	37	15	50	100	
W8/2/125/44	125	37	15	44	100	
W8/3/125	125	37	10	48	100	
W8/1/140	140	37	20	49	125	
W8/2/140	140	37	20	49	125	
W8/3/140	140	37	12	49	125	
W8/1/150	150	37	20	49	130	
W8/2/150	150	37	20	49	130	
W8/3/150	150	37	12	49	130	
W8/1/160	160	40	20	58	135	
W8/2/160	160	40	20	60	135	
W8/3/160	160	40	12	54	135	
W8/1/180	180	50	20	58	170	
W8/2/180	180	50	20	60	170	
W8/3/180	180	50	20	54	170	
W8/1/200	200	50	25	58	205	
W8/2/200	200	50	20	60	205	
W8/2/200/25	200	50	25	60	205	
W8/3/200	200	50	20	54	205	
W8/3/210	210	80	25	57	300	
W8/1/225	225	50	25	58	250	
W8/2/225	225	50	20	58	250	
W8/2/225/25	225	50	25	60	250	
W8/3/225	225	50	20	54	250	
W8/1/250	250	60	25	75	295	
W8/2/250	250	60	25	75	295	
W8/3/250	250	60	25	79	295	
W8/1/280	280	60	25	75	385	
W8/2/280	280	60	25	75	385	
W8/3/280	280	60	25	79	385	
W8/1/300	300	55	20	70	200	
W8/1/350	350	70	35	80	200	
W8/1/385	385	80	35	80	300	
W8/2/400	400	75	25	75	475	

schwarze Bereifung / Black rubber tire

Räder Wheels Code:						
	mm	mm	mm	mm	Kg	
W8/1/80/G	80	30	15	39	50	
W8/2/80/G	80	30	12	40	50	
W8/3/80/G	80	30	8	38	50	
W8/1/100/G	100	30	15	39	70	
W8/2/100/G	100	30	12	40	70	
W8/3/100/G	100	30	8	37	70	
W8/1/125/G	125	37	15	49	100	
W8/2/125/G	125	37	15	50	100	
W8/2/125/44/G	125	37	15	44	100	
W8/3/125/G	125	37	10	48	100	
W8/1/140/G	140	37	20	49	125	
W8/2/140/G	140	37	20	49	125	
W8/3/140/G	140	37	12	49	125	
W8/1/150/G	150	37	20	49	130	
W8/2/150/G	150	37	20	49	130	
W8/3/150/G	150	37	12	49	130	
W8/1/160/G	160	40	20	58	135	
W8/2/160/G	160	40	20	60	135	
W8/3/160/G	160	40	12	54	135	
W8/1/180/G	180	50	20	58	170	
W8/2/180/G	180	50	20	60	170	
W8/3/180/G	180	50	20	54	170	
W8/1/200/G	200	50	25	58	205	
W8/2/200/G	200	50	20	60	205	
W8/2/200/25/G	200	50	25	60	205	
W8/3/200/G	200	50	20	54	205	
W8/1/225/G	225	50	25	58	250	
W8/2/225/G	225	50	20	58	250	
W8/2/225/25/G	225	50	25	60	250	
W8/3/225/G	225	50	20	54	250	
W8/1/250/G	250	60	25	75	295	
W8/2/250/G	250	60	25	75	295	
W8/3/250/G	250	60	25	79	295	
W8/1/280/G	280	60	25	75	385	
W8/2/280/G	280	60	25	75	385	
W8/3/280/G	280	60	25	79	385	

graue Bereifung / Grey rubber tire