

## Elastik-Räder

**Rad:** Radkörper aus stoß- und schlagfestem Kunststoff. Ausgerüstet mit Elastikbereifung.

## Elastic wheels

**Wheel:** Wheel centre out of plastic, equipped with elastic rubber tyre.



Räder Wheels						
Code:	mm	mm	mm	mm	Kg	
W14/2/80	80	30	12	40	100	
W14/2/100	100	30	12	40	150	
W14/2/100/1	100	38	15	45	200	
W14/3/100	100	30	12	40	150	
W14/3/100/1	100	38	15	48	200	
W14/2/125	125	35	15	48	200	
W14/3/125	125	40	15	48	200	
W14/2/150	150	50	20	58	300	
W14/3/150	150	50	20	58	300	
W14/2/160	160	42	20	60	300	
W14/2/160	160	50	20	58	300	
W14/3/160	160	50	20	58	300	
W14/2/200	200	50	20	58	400	
W14/3/200	200	50	20	58	400	
W14/2/250	250	50	25	60	450	
W14/3/250	250	50	25	60	450	

blaue Bereifung / blue elastic-rubber tire  
Härte ca. 65° Shore A / Hardness abt. 65° Shore A



Räder Wheels						
Code:	mm	mm	mm	mm	Kg	
W14/2/80/GR	80	30	12	40	100	
W14/2/100/GR	100	30	12	40	150	
W14/2/125/GR	125	35	15	48	200	
W14/2/160/GR	160	42	20	58	300	
W14/2/200/GR	200	50	20	58	400	

grüne Bereifung / green elastic-rubber tire  
Härte ca. 65° Shore A / Hardness abt. 65° Shore A



Räder Wheels						
Code:	mm	mm	mm	mm	Kg	
W14/2/80/S	80	30	12	40	100	
W14/2/100/S	100	30	12	40	150	
W14/2/125/S	125	35	15	48	200	
W14/2/160/S	160	42	20	58	300	
W14/2/200/S	200	50	20	58	400	

schwarze Bereifung / black elastic-rubber tire  
Härte ca. 65° Shore A / Hardness abt. 65° Shore A



Räder Wheels						
Code:	mm	mm	mm	mm	Kg	
W14/2/80/G	80	30	12	40	100	
W14/2/100/G	100	30	12	40	150	
W14/2/125/G	125	40	15	48	200	
W14/2/160/G	160	50	20	58	300	
W14/2/200/G	200	50	20	58	400	

graue Bereifung / Grey elastic-rubber tire  
Härte ca. 65° Shore A / Hardness abt. 65° Shore A

