

## Schwerlast-Polyurethan-Räder

Rad: Radkörper aus Aluminium oder Guss mit Polyurethanbelag.

## Heavy duty Polyurethane wheels

Wheel: Wheel centre out of aluminium or grey special casting, equipped with polyurethane tyre.

Varianten / Zubehör  
Versions / accessory



Räder Wheels Code:	mm	mm	mm	mm	Kg	
W12/3/80	80	36	15	36	250	HH
W12/3/80/1	80	20	12	20	150	HH
W12/3/100	100	30	15	30	250	HH
W12/3/100/1	100	40	20	40	300	HH
W12/3/100/2	100	50	20	60	400	HH
W12/3/125	125	40	20	40	400	HH
W12/3/125/1	125	50	20	60	500	HH
W12/3/125/2/RO	125	60	20	60	700	HH
W12/3/150	150	40	20	40	500	HH
W12/3/150/1	150	50	25	50	800	HH
W12/3/150/2/RO	150	60	25	65	930	HH
W12/3/160/RO	160	40	20	58	700	HH
W12/3/160/1/RO	160	50	20	60	800	HH
W12/3/175	175	40	20	40	650	HH
W12/3/175/1/RO	175	40	20	52	720	HH
W12/3/175/2/RO	175	60	20	60	850	HH
W12/3/180/RO	180	50	25	60	900	HH
W12/3/200	200	50	25	60	1100	HH
W12/3/200/1/RO	200	60	25	65	1200	HH
W12/3/200/2/RO	200	80	30	80	1500	HH
W12/3/200/3/RO	200	100	30	100	1950	HH
W12/3/225/RO	225	50	25	50	1000	HH
W12/3/250	250	60	25	60	1400	HH
W12/3/250/1	250	80	30	80	1800	HH
W12/3/250/2/RO	250	100	35	100	2200	HH
W12/3/300	300	70	30	70	2200	HH
W12/3/300/1/RO	300	100	40	100	3000	HH
W12/3/300/2/RO	300	80	30	80	2200	HH
W12/3/350/RO	350	100	50	100	3500	HH
W12/3/400	400	100	40	100	4000	HH
W12/3/400/1	400	125	40	125	4600	HH
W12/3/500	500	100	50	100	4500	HH

Gussfelge / special casting rim  
PU Bereifung Härte ca. 95° Shore A  
PU tire hardness abt. 95° Shore A



Räder Wheels Code:	mm	mm	mm	mm	Kg	
W11/3/80	80	30	12	40	180	HH
W11/3/100	100	40	12	40	280	HH
W11/3/125	125	40	20	50	350	HH
W11/3/160	160	50	20	60	500	HH
W11/3/175	175	50	20	60	600	HH
W11/3/180	180	50	20	60	700	HH
W11/3/200	200	50	25	60	800	HH
W11/3/250	250	60	30	60	1000	HH

Aluminiumfelge / aluminium rim  
PU Bereifung Härte ca. 95° Shore A  
PU tire hardness abt. 95° Shore A



Räder Wheels Code:	mm	mm	mm	mm	Kg	
W12/3/100/VR/S80	100	40	20	50	300	HH
W12/3/125/VR/S80	125	50	20	60	400	HH
W12/3/150/VR/S80	150	50	20	60	500	HH
W12/3/200/VR/S80	200	50	25	60	650	HH
W12/3/250/VR/S80	250	50	30	60	800	HH
W12/3/250/VR/1/S80	250	80	30	85	950	HH
W12/3/300/VR/S80	300	75	30	75	1250	HH

Gussfelge / special casting rim  
PU Bereifung Härte ca. 80° Shore A  
PU tire hardness abt. 80° Shore A

