





















Polyamid Seilrollen








Rad: aus Polyamid 6,
gleitgelagert oder kugelgelagert
mit halbrunder Nut.

Polyamide pulleys

Wheel: out of
polyamide 6, with plain
or ball bearing and half
round slot.

Code:					Kg	Nut	
W57/40	40/32	12	6	15	35	8	
W57/48	48/40	12	8	15	42	8	
W57/50	50/40	10	15	11	30	4	
W57/60	60/38	30	12	18	90	20	
W57/65	65/57	12	8	15	50	8	
W57/73	73/65	13	10	17	55	8	
W57/76	76/66	15	11	17	75	11	
W57/80	80/62	22	12	25	140	12	
W57/90	90/70	18	10	21	130	10	
W57/100	100/84	12	10	17	85	3,5	
W57/100/2	100/74	25	15	28	160	18	
W57/100/3	100/68	42	20	27	270	28	
W57/120	120/88	27	15	33	300	18	
W57/126	126/102	34	30	42	500	14	
W57/150	150/110	33	20	42	410	25	



W560/40	40/30	13	8	5	50	5	
W560/50	50/38	13	10	5	50	4	
W560/65	65/55	12	10	5	135	8	
W560/78	78/56	15	10	5	135	8	
W560/78/2	78/66	19	15	10	245	12	
W560/80	80/50	21	15	10	125	8	
W560/98	98/80	20	10	20	150	6	



Andere Ausführungen auf Anfrage / Other versions on request

















Polyamid Spurkranzräder

Rad: Radkörper aus Polyamid 6.

Polyamide Flange wheels

Wheel: Wheel centre
out of polyamide 6.

Code:		Radbreite m. Spurk. mm	Radbreite o. Spurk. mm			Naben- 	Kg	
W0/SPG/30	30/50	20	15	20	10	-	35	
W0/SPG/35	35/50	32	25	34	16	30	80	
W0/SPG/40	40/55	18	12	18	15	-	40	
W0/SPG/50	50/70	30	20	30	16	-	100	
W0/SPG/50/1	50/65	32	24	29	15	-	100	
W0/SPG/62	62/80	26	18	30	16	35	100	
W0/SPG/87	87/108	32	25	32	16	-	200	
W0/SPG/100	100/120	45	32	40	20	50	280	
W0/SPG/120	120/150	42	30	45	38	80	380	

Andere Ausführungen auf Anfrage / Other versions on request