



Räder Wheels						
Code:	mm	mm	mm	mm	Kg	
W1/1/50	50	25	6	28	100	
W1/1/65	65	30	7	34	150	
W1/1/75	75	35	10	40	200	
W1/1/80	80	35	10	39	250	
W1/1/100	100	35	12	44	350	
W1/1/125	125	35	12	49	450	
W1/1/150	150	50	15	58	650	
W1/1/160	160	50	15	57	650	
W1/1/175/RO	175	45	20	58	430	
W1/1/175/1	175	50	15	57	750	
W1/1/175/RO/2	175	50	20	52	1200	
W1/1/200	200	50	20	58	1000	
W1/1/250	250	60	20	67	1250	
W1/1/250/1	250	60	25	65	1250	

Teilweise blau lackiert - bitte erfragen
Partial blue lacquered - please ask



bis 46.000 Kg
Up to 46.000 Kg



Material: Stahl
beständig von -40°C bis +140°C
Material: steel
Resistant from -40°C to +140°C

Räder Wheels						
Code:	mm	mm	mm	mm	Kg	
W1/3/75/ST	75	60	30	60	2300	
W1/3/100/ST	100	40	25	44	1700	
W1/3/100/1/ST	100	60	45	60	3100	
W1/3/125/ST	125	55	30	60	2750	
W1/3/150/ST	150	55	45	60	4000	
W1/3/150/1/ST*	150	80	40	80	6200	
W1/3/200/ST	200	55	50	60	6000	
W1/3/200/1/ST	200	80	60	90	7000	
W1/3/200/2/ST*	200	90	50	90	9300	
W1/3/225/ST	225	100	70	100	11600	
W1/3/250/ST	250	65	70	75	10000	
W1/3/250/1/ST	250	100	75	100	12900	
W1/3/300/ST	300	100	75	100	14680	
W1/3/350/ST	350	110	75	110	14680	
W1/3/350/1/ST*	350	110	75	110	19900	
W1/3/450/ST*	450	125	100	125	29000	
W1/3/600/ST*	600	150	150	150	46300	

* Schrägrollenlagerung / Tapered roller bearing

Mit Gehäusen auf Anfrage / With castors on request

Gussräder

Rad: Radkörper aus
Grauguss, beständig von
-40°C bis zu +500°C*.

Cast iron wheels

Wheel: Wheel centre
out of raw grey casting,
resistant from -40°C up
to +500°C*.

* In der Gleitlagerausführung / Only plain bearing version



Räder Wheels						
Code:	mm	mm	mm	mm	Kg	
W1/3/80	80	35	10	40	450	
W1/3/85/RO	85	25	15	36	250	
W1/3/100	100	30	15	30	300	
W1/3/100/1	100	40	12	44	500	
W1/3/100/2	100	40	20	50	750	
W1/3/125	125	32	15	32	400	
W1/3/125/1	125	45	12	50	500	
W1/3/150	150	38	20	38	600	
W1/3/150/1/RO	150	40	20	52	900	
W1/3/175	175	38	20	38	1000	
W1/3/175/1	175	50	15	57	750	
W1/3/175/2/RO	175	40	25	52	1000	
W1/3/200	200	48	25	48	1000	
W1/3/225/RO	225	50	25	65	1500	
W1/3/250	250	60	20	67	1250	
W1/3/270	270	70	30	70	2100	
W1/3/300	300	75	30	85	1500	
W1/3/325/RO	325	100	40	100	3600	
W1/3/470/RO	470	100	50	100	4800	

Andere Abmessungen auf Anfrage
Other versions on request



Räder Wheels						
Code:	mm	mm	mm	mm	Kg	
W1/2/80	80	35	10	42	250	
W1/2/100	100	35	10	44	350	
W1/2/100/1	100	35	12	50	300	
W1/2/100/2	100	45	12	50	400	
W1/2/125	125	35	12	50	450	
W1/2/150	150	50	15	57	650	
W1/2/175	175	50	15	57	650	
W1/2/200	200	50	20	58	1000	
W1/2/250	250	60	20	67	1250	