



Varianten / Zubehör  
Versions / accessory



Autoklavierbare Rollen auf Anfrage  
Autoclavable castors on request

Edelstahl-Rollen

Stainless Steel castors

Gehäuse: Edelstahl, alle Einbauteile sind komplett rostbeständig.

Housing: Stainless steel housing, all fitted components are completely rust resistant.



Thermoplastische Räder, gleitgelagert.  
Thermoplastic rubber wheel, plain bore.

Lenkrolle  
Swivel castors  
Code:

Lenkrolle Stop  
Swivel castors lock  
Code:

Bockrolle  
Fixed castors  
Code:



Code:	Code:	Code:	mm	mm	mm	mm	mm	Kg	
W6338/1/50/1	W6338/F/1/50/1	-	50	18	69	25	11	40	
W6368/1/60/1	W6368/F/1/60/1	-	60	20	88	25	12	50	
W6338/1/75/1	W6338/F/1/75/1	-	75	25	100	24	11	75	
W6368/1/80/1	W6368/F/1/80/1	-	80	22	108	26	12	50	
W6368/1/100/1	W6368/F/1/100/1	-	100	30	134	35	12	80	
W6338/1/125/1	W6338/F/1/125/1	-	125	30	159	35	12	80	



Polyamid, gleitgelagert.  
Polyamide, plain bore.

Lenkrolle  
Swivel castors  
Code:

Lenkrolle Stop  
Swivel castors lock  
Code:

Bockrolle  
Fixed castors  
Code:



Code:	Code:	Code:	mm	mm	mm	mm	mm	mm	mm	Kg	
W6338/1/50/3	W6338/F/1/50/3	W6334/1/50/3	50	18	69	25	60x60	48x48	6,3	40	
W6368/1/60/3	W6368/F/1/60/3	W6365/1/60/3	60	20	91	25	60x60	45x45	6,3	40	
W6338/1/75/3	W6338/F/1/75/3	W6334/1/75/3	75	25	100	24	60x60	48x48	8,5	75	
W6368/1/80/3	W6368/F/1/80/3	W6365/1/80/3	80	22	111	26	60x60	45x45	6,3	50	
W6368/1/100/3	W6368/F/1/100/3	W6365/1/100/3	100	30	134	35	76x70	60x50	8,3	80	
W6368/1/125/3	W6368/F/1/125/3	W6365/1/125/3	125	30	159	35	76x70	60x50	8,3	80	



Polyurethan 92° Shore A, Alufelge, Kugellagerung, **antistatisch**, Ableitwiderstand 5x10 hoch 7 Ohm  
Polyurethane wheel, **antistatic**, resistance 5x10 high 7 Ohm, 92° Shore A, aluminium rim, ball bearing

Lenkrolle  
Swivel castors  
Code:

Lenkrolle Stop  
Swivel castors lock  
Code:

Bockrolle  
Fixed castors  
Code:



Code:	Code:	Code:	mm	mm	mm	mm	mm	mm	mm	Kg	
W11460/3/80/P4/AS	W11460/F/3/80/P4/AS	W11459/3/80/P4/AS	80	30	108	47	100x84	80x60	9	140	
W11460/3/100/P4/AS	W11460/F/3/100/P4/AS	W11459/3/100/P4/AS	100	30	128	47	100x84	80x60	9	160	
W11460/3/125/P5/AS	W11460/F/3/125/P5/AS	W11459/3/125/P5/AS	125	30	155	51	100x84	80x60	9	200	
W11460/3/150/P5/AS	W11460/F/3/150/P5/AS	W11459/3/150/P5/AS	150	40	195	45	132x110	105x80	11,5	320	
W11460/3/160/P6/AS	W11460/F/3/160/P6/AS	W11459/3/160/P6/AS	160	50	200	60	132x110	105x80	12	400	
W11460/3/175/P6/AS	W11460/F/3/175/P6/AS	W11459/3/175/P6/AS	175	50	230,5	59	132x110	105x80	12	480	
W11460/3/200/P6/AS	W11460/F/3/200/P6/AS	W11459/3/200/P6/AS	200	50	243	59	132x110	105x80	12	640	