



Version / accessory: **directional lock**
Varianten / Zubehör: **Richtungsfeststeller**

Antistatic-Schwerlast-Polyurethan-Rollen

Rad: Polyurethanbelag in 91° Shore A Härte grau nach RAL 7037, kugelgelagert.
Gehäuse: aus dickwandigem verzinktem Stahlblech gepreßt. Doppelte Kugellagerung im Gabelkopf.

Antistatic-heavy-polyurethane castors

Wheel: Polyurethane tread with 91° Shore A hardness. Colour RAL 7037, ball bearing.
Housing: steel-welded construction, with double ball bearing in the fork head.



Gussfelge, kugelgelagert, Ableitwiderstand 5 x 10 hoch 7 Ohm
Wheel center out of grey casting, ball bearing, resistance 5 x 10 high 7 Ohm

Lenkrolle
Swivel castors
Code:

Lenkrolle Stop
Swivel castors lock
Code:

Bockrolle
Fixed castors
Code:



Code:	Code:	Code:	mm	mm	mm	mm	mm	mm	mm	mm	Kg
W1241/3/80/P4/AS	W1241/F3/80/P4/AS	W1239/3/80/P4/AS	80	36	108	47	100x84	80x60	9	200	
W1241/3/100/P4/AS	W1241/F3/100/P4/AS	W1239/3/100/P4/AS	100	30	128	47	100x84	80x60	9	200	
W1241/3/100/P4/S/AS	W1241/F3/100/S/AS	W1239/3/100/S/AS	100	40	125	48	135x110	105x80	10,5	240	
W1241/3/125/P5/AS	W1241/F3/125/P5/AS	W1239/3/125/P5/AS	125	40	161	51	100x84	80x60	9	320	
W1241/3/125/S/AS	W1241/F3/125/S/AS	W1239/3/125/S/AS	125	40	155	40	135x110	105x80	10,5	250	
W1241/3/150/P5/AS	W1241/F3/150/P5/AS	W1239/3/150/P5/AS	150	40	188	45	132x110	105x80	11,5	400	
W1241/3/175/P6/AS	W1241/F3/175/P6/AS	W1239/3/175/P6/AS	175	40	230,5	59	132x110	105x80	12	520	
W1241/3/200/P6/AS	W1241/F3/200/P6/AS	W1239/3/200/P6/AS	200	50	243	59	132x110	105x80	12	700	



Aluminiumfelge, kugelgelagert, Ableitwiderstand 5 x 10 hoch 7
Wheel center out of aluminium, ball bearing, resistance 5 x 10 high 7

Lenkrolle
Swivel castors
Code:

Lenkrolle Stop
Swivel castors lock
Code:

Bockrolle
Fixed castors
Code:



Code:	Code:	Code:	mm	mm	mm	mm	mm	mm	mm	mm	Kg
W1141/3/80/P4/AS	W1141/F3/80/P4/AS	W1139/3/80/P4/AS	80	30	108	47	100x84	80x60	9	140	
W1141/3/100/P4/AS	W1141/F3/100/P4/AS	W1139/3/100/P4/AS	100	30	128	47	100x84	80x60	9	160	
W1141/3/100/S/AS	W1141/F3/100/S/AS	W1139/3/100/S/AS	100	40	125	48	135x110	105x80	10,5	225	
W1141/3/125/P5/AS	W1141/F3/125/P5/AS	W1139/3/125/P5/AS	125	30	161	51	100x84	80x60	9	200	
W1141/3/125/S/AS	W1141/F3/125/S/AS	W1139/3/125/S/AS	125	40	155	40	135x110	105x80	10,5	250	
W1141/3/150/P5/AS	W1141/F3/150/P5/AS	W1139/3/150/P5/AS	150	40	188	45	132x110	105x80	11,5	320	
W1141/3/160/P6/AS	W1141/F3/160/P6/AS	W1139/3/160/P6/AS	160	50	200	60	132x110	105x80	12	400	
W1141/3/175/P6/AS	W1141/F3/175/P6/AS	W1139/3/175/P6/AS	175	50	230,5	59	132x110	105x80	12	480	
W1141/3/200/P6/AS	W1141/F3/200/P6/AS	W1139/3/200/P6/AS	200	50	243	59	132x110	105x80	12	640	