

Piktogramme
 Pictographs

 Rad \varnothing
 Wheel \varnothing

 Radbreite
 Wheel width

 Bauhöhe
 Overall height

 Plattengröße
 Plate size

 Lochabstand
 hole spacing

 Weich
 Soft

 Gleitlager
 Plain bearing

 Schwerlast
 Heavy duty castors

 Loch \varnothing
 Hole \varnothing

 Tragkraft in Kg
 Load capacity Kg

 Bohrungs \varnothing
 Bearing bore \varnothing

 Nabenlänge
 Hub length

 Ausladung Lenk.
 Offset

 Super Elastik weich
 Super elastic soft

 Rollenlager
 Roller bearing

 Spurfrei
 tracefree (floor protective)

 \varnothing Rückenlochbohrung
 Bolt hole \varnothing

 antistatisch / elektr. leitfähig
 Antistatic / electrical conductive


 rostfreie Ausführung
 Stainless steel

 Hitzebeständig
 Heat resistant

 Elastik weich
 Elastic soft

 verstärkt
 extra-strong

 Kugellager
 Ball bearing

Befestigungen für
Rückenlochbohrung
 fixing for single bolt hole

 Rundrohrmaß
 round tube

Code

 18-20mm
 21-23mm
 24-27mm
 28-31mm

 W/Bef.4/R18-20
 W/Bef.4/R21-23
 W/Bef.4/R24-27
 W/Bef.4/R28-31

 Vierkantrrohr
 square tube

Code

 18-20mm
 21-23mm
 24-27mm
 28-31mm
 36-38mm

 W/Bef.4/V18-20
 W/Bef.4/V21-23
 W/Bef.4/V24-27
 W//Bef.4/V28-31
 W/Bef.4/V36-28

 Zapfenmaß
 steel pin size

Code

 17mm
 18mm
 19mm
 20mm
 21mm
 22mm
 23mm

 W/Bef./AZ/R17
 W/Bef./AZ/R18
 W/Bef./AZ/R19
 W/Bef./AZ/R20
 W/Bef./AZ/R21
 W/Bef./AZ/R22
 W/Bef./AZ/R23

 Zapfenmaß
 steel pin size

Code

 24mm
 25mm
 26mm
 27mm
 28mm
 29mm

 W/Bef./AZ/R24
 W/Bef./AZ/R25
 W/Bef./AZ/R26
 W/Bef./AZ/R27
 W/Bef./AZ/R28
 W/Bef./AZ/R29

Reduzierhülse / Bolt hole bushing

 W/RH/12/10 \varnothing 12 >> \varnothing 10mm