

**Elektrisch leitfähige
Edelstahl-Rollen**

Rad: Radkörper aus stoß- und schlagfestem Kunststoff.
Gehäuse: Edelstahl, alle Einbauteile (außer Kugellager) sind komplett rostbeständig, Ableitwiderstand < 10.000 Ohm (10 hoch 4).

Electrical conductive stainless steel castors
Wheel: Wheel centre out of plastic.
Housing: Stainless steel housing, all fitted (except ball bearing) components are completely rust resistant, resistance < 10.000 Ohm (10 high 4).



Varianten / Zubehö
Versions / accessor



Autoklavierbare Rollen auf Antrag
Autoclavable castors on request



Thermoplastische Polyurethanrollen, kugellagert, alle Einbauteile (außer Kugellager) sind komplett rostbeständig.
Thermoplastic polyurethane castors, ball bearing, all fitted (except ball bearing) components are completely rust resistant.

Lenkrolle Swivel castors Code:	Lenkrolle Stop Swivel castors lock Code:	Bockrolle Fixed castors Code:							
			mm	mm	mm	mm	mm	Kg	
W9460/3/80/1/AS	W9460/F3/80/1/AS	-	80	25	108	32	12	100	
W9460/3/100/1/AS	W9460/F3/100/1/AS	-	100	32	128	32	12	150	
W9460/3/125/1/AS	W9460/F3/125/1/AS	-	125	32	155	32	12	160	
W9460/3/160/1/AS	W9460/F3/160/1/AS	-	160	46	197	52	12	350	
W9460/3/200/1/AS	W9460/F3/200/1/AS	-	200	50	88	49	12	350	



Thermoplastische Polyurethanrollen, kugellagert, alle Einbauteile (außer Kugellager) sind komplett rostbeständig.
Thermoplastic polyurethane castors, ball bearing, all fitted (except ball bearing) components are completely rust resistant.

Lenkrolle Swivel castors Code:	Lenkrolle Stop Swivel castors lock Code:	Bockrolle Fixed castors Code:									
			mm	mm	mm	mm	mm	mm	mm	Kg	
W9460/3/80/AS	W9460/F3/80/AS	W9459/3/80/AS	80	32	108	32	100x80	80x60	9	125	
W9460/3/100/AS	W9460/F3/100/AS	W9459/3/100/AS	100	32	128	32	100x80	80x60	9	150	
W9460/3/125/AS	W9460/F3/125/AS	W9459/3/125/AS	125	32	155	32	100x80	80x60	9	160	
W9460/3/160/AS	W9460/F3/160/AS	W9459/3/160/AS	160	46	197	52	130x106	105x80	11	350	
W9460/3/200/AS	W9460/F3/200/AS	W9459/3/200/AS	200	50	240	49	130x106	105x80	11	350	



Schwerlast-Thermoplastische Polyurethanrollen, kugellagert, alle Einbauteile (außer Kugellager) sind komplett rostbeständig.
Heavy duty thermoplastic polyurethane castors, ball bearing, all fitted (except ball bearing) components are completely rust resistant.

Lenkrolle Swivel castors Code:	Lenkrolle Stop Swivel castors lock Code:	Bockrolle Fixed castors Code:									
			mm	mm	mm	mm	mm	mm	mm	Kg	
W9460/3/80/P4/AS	W9460/F3/80/P4/AS	W9459/3/80/P4/AS	80	32	108	47	100x84	80x60	9	130	
W9460/3/100/P4/AS	W9460/F3/100/P4/AS	W9459/3/100/P4/AS	100	32	128	47	100x84	80x60	9	150	
W9460/3/125/P5/AS	W9460/F3/125/P5/AS	W9459/3/125/P5/AS	125	32	161	51	100x84	80x60	9	160	
W9460/3/125/P6/AS	W9460/F3/125/P6/AS	W9459/3/125/P6/AS	125	46	164,5	61	132x110	105x80	12	400	
W9460/3/150/P5/AS	W9460/F3/150/P5/AS	W9459/3/150/P5/AS	150	32	188	45	132x110	105x80	11,5	180	
W9460/3/160/P6/AS	W9460/F3/160/P6/AS	W9459/3/160/P6/AS	160	46	200	60	132x110	105x80	12	450	
W9460/3/200/P6/AS	W9460/F3/200/P6/AS	W9459/3/200/P6/AS	200	50	243	59	132x110	105x80	12	500	